# Iridium Extreme 9575PTT

**Brand:** IRIDIUM
**Product Code:** 11-103_FPKT1901
**Availability:** upon request

## Price: Fr. 2095.00

**Ex Tax: Fr. 1938.02**

### Short Description

The waterproof and impact-resistant Iridium satellite phone with emergency call function and push to talk function for extreme missions around the globe.

### Description

The waterproof and impact-resistant Iridium satellite phone with emergency call function for extreme missions around the globe.

Special feature: The 9575 PTT is equipped with a push-to-talk function (talk button), which allows to establish a kind of radiotelephone connection to other participants of a closed group via satellite. A special contract is required for this.

A suitable Iridium SIM card is required for operation:

- Iridium postpaid SIM with monthly subscription
- Iridium Prepaid SIM with credit

Select the appropriate SIM card under "Accessories and similar products"!

Translated with www.DeepL.com/Translator (free version)

### Lieferumfang

- Battery 2'300 mAh

- Travel charger for mains operation incl. 5 adapters
- Mobile charger with lighter plug
- Protective cover
- USB data cable
- User Manual (English only)
- Quick Start Guide
- CD-ROM with software
- Accessory adapter (2x)
- Magnetic vehicle antenna with 1.5m cable
- Hand-free set with earphone and microphone

**Specifications**

| | |
|---|---|
| Communication specs | |
| Antenna type | Teleskop ausziehbar |
| Coverage | weltweit |
| Data transmission | 2400 bit/s (komprimiert 9600 bit/s |
| Frequency range | 1616.0 - 1626.5 MHz |
| Provider | Iridium |
| Stand by time max. | 30 h |
| Talking time max. | 4 h |
| Construction / technical data | |
| Data connection | Mini-USB |
| DC power voltage | 10-32 V= |
| Dimensions LxWxD | 140 x 60 x 27 mm |
| Display type | LCD |
| Main power voltage | 110-240 V~ |
| Weight | 247 g |
| Environmental conditions | |
| Charging temperatures | 0 °C bis +45 °C |
| Leak tightness | IP65 |
| Max. absolute altitude | 12'192 m.ü.M = 40'000 ft |
| Technical standards | MIL-STD 810F |
| Temperature range | -65 °C bis +71 °C |

**Product Gallery**

Iridium Extreme PTT
Push-to-Talk